



SAAK Tile GripX S951

DESCRIPTION :

A two-component, acrylic-modified cementitious material designed for surface roughening and bonding of existing ceramic and porcelain tiles, allowing the installation of new tiles or other finishes without removing the old tiles. The system consists of a powder and liquid component mixed on-site to form a high-adhesion layer with excellent crack-bridging properties and high resistance to alkalinity. Suitable for application on existing tiles, concrete, blockwork, and plastered surfaces in renovation and refurbishment works.

ADVANTAGE :

- Easy to use.
- Emulsion-based or can be mixed as a mortar.
- High adhesive strength to strong, sound surfaces.
- Water-resistant and non-toxic.
- Highly resistant to freezing, snow-melting salts.
- Suitable for drinking water.

USES:

- Surface roughening and bonding of existing tiles for tile-on-tile applications without removing old tiles.
- Improving adhesion on smooth, non-absorbent surfaces before tiling or cement-based finishes.
- Suitable for interior and exterior surfaces such as tiles, concrete, and plaster.

TECHNICAL DATA :

Appearance	Compound A: Gray powder Compound B: White liquid
Mixture density	1.65 g/cm ³ (Suitable consistency for brushing)
Mix ratio	1:4 liquid to powder
Coverage rate	1.8-2.0 kg per m ² thickness of 1mm
Tensile adhesion	>2.0 N/mm ²
Curing period	96 hrs
Standards	- ASTM D412 - BSEN 12390 - ASTM 542

Recommended Application:

The two components are mixed in a clean container using a low-speed electric mixer until a homogeneous mixture is obtained.

The material is applied using a brush or roller.

Allow the applied layer to dry for approximately 4 hours to achieve a highly roughened surface with strong adhesion.

Detailed mixing and application instructions are clearly indicated on the product packaging.

CLEANING :

Tools and equipment should be cleaned with water immediately after use. Hardened material should be removed mechanically

APPLICATION TOOLS :

- Brush.
- Roller.
- Spraying machine.

PACKAGING :

Compound A - 10 kg powder

Compound B - 2.5 liters liquid

COVERAGE :

30 to 40 m²



SAAK Tile GripX S951

LIFE & STORAGE :

Keep the product in dry covered shed at temperature between 25°C In these conditions, the product shelf life is 12 months.

HEALTH & SAFETY :

Keep away from direct sunlight and moisture.

- Keep out of reach of children.
- In case of contact with eyes and skin, rinse thoroughly with plenty of water.

